Project Name: CAN

Project Code: CAN Site ID: C534 Observation ID: 1

Agency Name: CSIRO Division of Soils (NSW)

Site Information

Desc. By: J. Loveday Locality: Tubbo site 12A-AM

 Date Desc.:
 01/12/61
 Elevation:
 150 metres

 Map Ref.:
 Sheet No.: 8128
 1:100000
 Rainfall:
 410

 Northing/Long.:
 146.08777777778
 Runoff:
 Very slow

Easting/Lat.: -34.666666666667 Drainage: Imperfectly drained

Geology

ExposureType: Soil pit Conf. Sub. is Parent. Mat.: No Data

Geol. Ref.: No Data Substrate Material: Slightly porous, Unconsolidated material

(unidentified)

Land Form

Rel/Slope Class:Level plain <9m <1%</th>Pattern Type:Alluvial plainMorph. Type:FlatRelief:No DataElem. Type:PlainSlope Category:LevelSlope:<1 %</th>Aspect:0 degrees

Surface Soil Condition (dry): Cracking

Erosion:

Soil Classification

Australian Soil Classification:Mapping Unit:N/AEpicalcareous Epipedal Brown VertosolPrincipal Profile Form:Ug5.34ASC Confidence:Great Soil Group:Grey clay

All necessary analytical data are available.

Site Disturbance: Cultivation. Irrigated, past or present

Vegetation: Low Strata - Forb, <0.25m, Closed or dense. *Species includes - None recorded

Surface Coarse Fragments: No surface coarse fragments

Profile Morphology

0 - 0.1 m Brown (7.5YR4/3-Dry); ; Medium heavy clay; 100-200 mm, Angular blocky; 200-500 mm,

Prismatic; Coarse, (10 - 20) mm crack; Very strong consistence; Few (2 - 10 %), Calcareous, ,

Concretions; Field pH 8.6 (pH meter);

0.1 - 0.51 m ; Medium heavy clay;

0.51 - 0.91 m Brown (7.5YR4/4-Moist); ; Medium heavy clay; 100-200 mm, Angular blocky; 200-500 mm,

Prismatic; Coarse, (10 - 20) mm crack; Very strong consistence; Few (2 - 10 %), Calcareous, ,

Concretions;

0.91 - 1.14 m Brown (7.5YR5/4-Moist); ; Medium heavy clay; 100-200 mm, Angular blocky; 200-500 mm,

Prismatic; Medium, (5 - 10) mm crack; Very strong consistence; Few (2 - 10 %), Calcareous, ,

Concretions;

1.14 - 1.24 m Brown (10YR5/3-Moist); , 5Y52; Medium heavy clay; 100-200 mm, Angular blocky; 200-500 mm,

Prismatic; Fine, (0 - 5) mm crack; Very strong consistence; Very few (0 - 2 %), Calcareous, ,

Concretions;

Morphological Notes

Observation Notes

TOP 10CM GRADED OFF

Site Notes

COLEAMBALLY

CAN

CAN Site ID: C534 CSIRO Division of Soils (NSW) Observation ID: 1

Project Name: Project Code: Agency Name:

Laboratory Test Results:

Depth	рН	1:5 EC		hangeable Vig	Cations K	Na	Exchangeable Acidity	CEC	I	ECEC	E	SP
m		dS/m		J		Cmol (+)/kg				%	, D
0 - 0.025	7.7A	0.15A										
0.025 - 0.1 0.1 - 0.2	8.1A	0.21A	24K	9.1	0.71	0.13	1.5E			35.4B		
0.2 - 0.3	8.6A	0.15A	22.9K	10.8	0.62	0.51				34.8B		
								_				
Depth	CaCO3	Organic C	Avail. P	Total P	Total N	Total K	Bulk Density	Pa GV	rticle CS	Size A	nalysis Silt C	lay
m	%	%	mg/kg	%	%	%	Mg/m3			%		
0 - 0.025									6D	25	9	58
0.025 - 0.1 0.1 - 0.2	0.81 <i>A</i>	0.51F							6D	22	10	60
0.2 - 0.3	1.59A	٨.							6D	24	10	59
Depth	COLE	COLE Gravimetric/Volumetric Water Contents K sat K unsat										
m	JJLL	Sat.	0.05 Bar	0.1 Bar	0.5 Bar g - m3/m3	1 Bar	5 Bar 15	Bar	mm/		mm/h	

0 - 0.025 0.025 - 0.1 0.1 - 0.2 0.2 - 0.3

Project Name: CAN

Project Code: CAN Site ID: C534 Observation ID: 1

Agency Name: CSIRO Division of Soils (NSW)

Laboratory Analyses Completed for this profile

15_NR_CA
Exch. basic cations (Ca++) - meq per 100g of soil - Not recorded
15_NR_K
Exch. basic cations (K++) - meq per 100g of soil - Not recorded
15_NR_MG
Exch. basic cations (Mg++) - meq per 100g of soil - Not recorded
15_NR_NA
Exch. basic cations (Na++) - meq per 100g of soil - Not recorded

15G1_H Hydrogen Cation - meq per 100g of soil - 1M KCl Exch. Acidity By titration to pH 8.0 Sum of Ex. cations + Ex. acidity - Sum of basic exch. cations and exch. (Hydrogen)

19A1 Carbonates - rapid titration
2_LOI Loss on Ignition (%)
3A1 EC of 1:5 soil/water extract
4A1 pH of 1:5 soil/water suspension

5A2 Chloride - 1:5 soil/water extract, automated colour

6_DC Organic carbon (%) - Dry combustion

P10_PB_C
P10_PB_CS
Clay (%) - Plummet balance
Coarse sand (%) - Plummet balance
P10_PB_FS
P10_PB_Z
Clay (%) - Plummet balance
Fine sand (%) - Plummet balance
Silt (%) - Plummet balance